

Ratings @ 0.8 PF		Prime Rating	Stand by Rating	Dimensions	
Voltage* ¹	Frequency*	KC1150* ³	KC1275S* ⁴	Length	4500 mm
220/380 V	60 Hz	1150 kVA	1275 kVA	Width	2050mm
127/220 V	60 Hz	1141 kVA	1260 kVA	Height	2400mm
277/480 V	60 Hz	1141 kVA	1263 kVA	Weight	6100 Kg

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1 standard.

Notes

1. The applicable voltage range is 220V, 380V to 480V for 60Hz applications. For other voltages, please consult factory.

2. This generating set is of fixed speed of 1800 rpm.

3. KC1150 is the prime power rating of the generating set is where a variable load and unlimited hour usage are applied with an average load factor of 80% of the prime rating over each 24-hour period. Noting that a 10% overload is permitted for 1 hour in every 12-hour operation.

4. KC1275S is the standby power rating of the generating set is where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

5. This rating level at voltage 220/380 is achieved when upsizing alternator to LSA50.2M6

Engine Technical Data

Make & Model	CUMMINS QST30-G4		
Cylinders & Arrangement	12; 50° Vee		
Bore & Stroke (mm)	140 x 165		
Induction system	Turbo Charged & Aftercooled		
Combustion	Direct injection		
Cycle	4 stroke		
Compression ratio	14.0:1		
Cooling System	Water cooled		
Displacement	30.5 liters		
Lube oil capacity	154 liters Max		
Coolant capacity	79 liters		
Standard governor (Optional)	Electronic		
Engine Speed	1800 rpm		
Fuel Consumption (L/H) @ 100% Load	240	@ 50% Load	119
Fuel Consumption (L/H) @ 75% Load	177	@ 25% Load	66
Radiator Cooling Air Flow (m ³ /s)	17.07		
Emissions regulations	For non-regulated territories		
Exhaust temperature °C (max)	495		
Max exhaust gas flow (m ³ /min)	197.1		
Max. allowed back pressure (kPa)	7.0		

The above performance data are valid as per the following specs:

- Diesel Fuel is accorg to BS2869 Class A2 or equivalent.
- Lubricating oil is according to Grade SAE 15W-40 API CI4.
- The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data

Make & Model	Leroy Somer OR Stanford TAL049E / Leroy Somer OR Stanford LSA50.2M6				
Frequency / No. of poles	60Hz / 4P	60Hz / 4P	Winding pitch	2/3	2/3
Ingress protection	IP23	IP23	AVR model	R150	R450
Insulation class	H	H	Overspeed	2250 R.P.M.	2250 R.P.M.
Terminals (Optional)	6 (12)	6 (12)	Voltage regulation	$\pm 1\%$	$\pm 1\%$
Excitation system	SHUNT	AREP	Coolant air flow	1.2 m ³ /s	2.2 m ³ /s