

Ratings @ 0.8 PF		Prime Rating	Stand by Rating
Voltage*1	Frequency*2	KC150*3	KC165S*4
220/380 V	60 Hz	148 kVA	163 kVA
127/220 V	60 Hz	155 kVA	170 kVA
277/480 V	60 Hz	159 kVA	170 kVA

Dimensions	
Length	2500 mm
Width	950 mm
Height	1550 mm
Weight	1100 Kg

The above ratings represent the generating set capability guaranteed within  $\pm 3\%$  at the reference conditions equivalent to those specified in ISO 8528/1 standard.

### Notes

1. The applicable voltage range is 220V, 380V to 480V for 60Hz applications. For other voltages, please consult factory.

2. This generating set is of fixed speed of 1800 rpm.

3. KC150 is the prime power rating of the generating set is where a variable load and unlimited hour usage are applied with an average load factor of 80% of the prime rating over each 24-hour period. Noting that a 10% overload is permitted for 1 hour in every 12-hour operation.

4. KC165S is the standby power rating of the generating set is where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

5. This rating level at voltage 220/380 is achieved when upsizing alternator to TAL044J

### Engine Technical Data

Make & Model	CUMMINS 6BTAA5.9-G6		
Cylinders & Arrangement	6; in-line		
Bore & Stroke (mm)	120 x 120		
Induction system	Turbo Charged & Aftercooled		
Combustion	Direct injection		
Cycle	4 stroke		
Compression ratio	16.5:1		
Cooling System	Water cooled		
Displacement	5.9 liters		
Lube oil capacity	16.4 liters Max		
Coolant capacity	21 liters		
Standard governor (Optional)	Electronic		
Engine Speed	1800 rpm		
Fuel Consumption (L/H) @ 100% Load	36.46	@ 50% Load	20.71
Fuel Consumption (L/H) @ 75% Load	31.47	@ 25% Load	11.71
Radiator Cooling Air Flow (m <sup>3</sup> /s)	3.7		
Emissions regulations	For non-regulated territories		
Exhaust temperature °C (max)	462		
Max exhaust gas flow (m <sup>3</sup> /min)	29.2		
Max. allowed back pressure (kPa)	10.25		

The above performance data are valid as per the following specs:

- Diesel Fuel is accorg to BS2869 Class A2 or equivalent.
- Lubricating oil is according to Grade SAE 15W-40 API CI4.
- The coolant should be 50% antifreeze and 50% fresh water.

### Alternator Technical Data

Make & Model	Leroy Somer TAL044H OR Stanford				
Frequency / No. of poles	60Hz / 4P	60Hz / 4P	Winding pitch	2/3	2/3
Ingress protection	IP23	IP23	AVR model	R120	R120
Insulation class	H	H	Overspeed	2250 R.P.M.	2250 R.P.M.
Terminals (Optional)	6 (12)	6 (12)	Voltage regulation	$\pm 1\%$	$\pm 1\%$
Excitation system	SHUNT	SHUNT	Coolant air flow	0.3 m <sup>3</sup> /s	0.3 m <sup>3</sup> /s