

Ratings @ 0.8 PF	Prime Rating	Stand by Rating
Voltage* ¹ Frequency* ²	KC2850* ³	KC3150S* ⁴
220/380 V 60 Hz	2850 kVA	3150 kVA

Dimensions	
Length	6000 mm
Width	2300 mm
Height	2500 mm
Weight	16300 Kg

The above ratings represent the generating set capability guaranteed within $\pm 3\%$ at the reference conditions equivalent to those specified in ISO 8528/1 standard.

Notes

1. The applicable voltage range is 220V, 380V to 480V for 60Hz applications. For other voltages, please consult factory.

2. This generating set is of fixed speed of 1800 rpm.

3. KC2850 is the prime power rating of the generating set is where a variable load and unlimited hour usage are applied with an average load factor of 80% of the prime rating over each 24-hour period. Noting that a 10% overload is permitted for 1 hour in every 12-hour operation.

4. KC3150S is the standby power rating of the generating set is where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

Engine Technical Data

Make & Model	CUMMINS QSK78-G7		
Cylinders & Arrangement	18; 60° Vee		
Bore & Stroke (mm)	170 x 190		
Induction system	Turbo Charged & Aftercooled		
Combustion	Direct injection		
Cycle	4 stroke		
Compression ratio	15.3:1		
Cooling System	Water cooled		
Displacement	77.6 liters		
Lube oil capacity	465.6 liters Max		
Coolant capacity	223.4 liters		
Standard governor (Optional)	Electronic		
Engine Speed	1800 rpm		
Fuel Consumption (L/H) @ 100% Load	611	@ 50% Load	345
Fuel Consumption (L/H) @ 75% Load	475	@ 25% Load	201
Radiator Cooling Air Flow (m ³ /s)	TBA		
Emissions regulations	For non-regulated territories		
Exhaust temperature °C (max)	433		
Max exhaust gas flow (m ³ /min)	536.1		
Max. allowed back pressure (kPa)	7.0		

The above performance data are valid as per the following specs:

- Diesel Fuel is accorg to BS2869 Class A2 or equivalent.
- Lubricating oil is according to Grade SAE 15W-40 API CI4.
- The coolant should be 50% antifreeze and 50% fresh water.

Alternator Technical Data

Make & Model	Leroy Somer OR Stanford LSA52.3L12 (8S)		
Frequency / No. of poles	60Hz / 4P	Winding pitch	2/3
Ingress protection	IP23	AVR model	D 510C
Insulation class	H	Overspeed	2250 R.P.M.
Terminals (Optional)	6 (12)	Voltage regulation	$\pm 0.5\%$
Excitation system	AREP + PMI	Coolant air flow	2.8 m ³ /s